

## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings of claims in the application:

### **Listing of Claims:**

Claims 1-5 (Cancelled)

Claim 6. (Previously Presented): A process for the production of an aqueous two-component polyurethane coating emulsion comprising pumping a mixture of at least one polyisocyanate and an aqueous binder dispersion under a pressure of 1 to 30 MPa into a disperser, said disperser comprising:

- a) a ceramic sleeve having bores or slots in the wall thereof, with said bores or slots communicating with one end of a pipe, said pipe having an open end remote from said end communicating with said bores or slots,
  - a1) said ceramic sleeve having an open end,
  - a2) said ceramic sleeve further having a moveable ceramic piston located opposite said open end,
    - a2i) with the movement of said moveable ceramic piston being such that flow through said bores or slots can be enabled or completely closed, and
    - a2ii) with said movement being caused either via a pneumatic drive or an electric step motor,

and wherein said mixture is pumped into the open end of said ceramic sleeve, through said bores or slots, and through said pipe.

Claim 7. (Previously Presented): The process of Claim 6, wherein said bores or slots are in the form of nozzle bores or slots.

Claim 8. (Currently Amended): A process for the production of an aqueous two-component polyurethane coating emulsion comprising pumping a mixture of at least one polyisocyanate and an aqueous binder dispersion under a pressure of 1 to 30 MPa into a ~~dispenser~~ dispenser, said ~~dispenser~~ dispenser comprising:

- b) a ceramic sleeve having bores or slots in the wall thereof, with said bores or slots communicating with one end of a pipe, said pipe having an open end remote from said end communicating with said bores or slots,
  - a1) said ceramic sleeve having an open end,
  - a2) said ceramic sleeve further having a moveable ceramic piston located opposite said open end,
    - a2i) with the movement of said moveable ceramic piston being such that flow through said bores or slots can be enabled or completely closed, and
    - a2ii) with said movement being caused either via a pneumatic drive or an electric step motor,

and wherein said mixture is pumped into said pipe, through said bores or slots and through said ceramic sleeve.

Claim 9. (Previously Presented): The process of Claim 8, wherein said bores or slots are in the form of nozzle bores or slots.